

§ 97.30-1

to keep a proper lookout or to maintain a proper fire watch or from any neglect of any precaution which may be required by the ordinary practice of seamen or by the special circumstances of the case. When circumstances require it, additional watches shall be maintained to guard against fire or other danger and to give an alarm in case of accident or disaster.

Subpart 97.30—Reports of Accidents, Repairs, and Unsafe Equipment

§ 97.30-1 Repairs to boilers and pressure vessels.

(a) Before making any repairs to boilers or unfired pressure vessels, the chief engineer shall submit a report covering the nature of the repairs to the Officer in Charge, Marine Inspection, at or nearest to the port where the repairs are to be made.

§ 97.30-5 Accidents to machinery.

(a) In the event of an accident to a boiler, unfired pressure vessel, or machinery tending to render the further use of the item unsafe until repairs are made, or if by ordinary wear such items become unsafe, a report shall be made, by the chief engineer immediately to the Officer in Charge, Marine Inspection, or if at sea immediately upon arrival at port.

§ 97.30-10 Notice required before repair.

(a) No repairs or alterations, except in an emergency, shall be made to any lifesaving or fire detecting or extinguishing equipment without advance notice to the Officer in Charge, Marine Inspection. When emergency repairs or alterations have been made, notice shall be given to the Officer in Charge, Marine Inspection, as soon as practicable.

Subpart 97.33—Communication Between Deckhouses

§ 97.33-1 When required.

On all vessels navigating in other than protected waters, where the distance between deckhouses is more than 46 meters (150 feet) a fixed means facili-

46 CFR Ch. I (10-1-98 Edition)

tating communication between both ends of the vessel, such as a raised fore and aft bridge or side tunnels, must be provided. Previously approved arrangements may be retained so long as they are maintained in good condition to the satisfaction of the Officer in Charge, Marine Inspection.

[CGD 95-027, 61 FR 26007, May 23, 1996]

Subpart 97.34—Work Vests

§ 97.34-1 Application.

(a) Provisions of this subpart shall apply to all vessels inspected and certificated in accordance with this subchapter.

§ 97.34-5 Approved types of work vests.

(a) Each buoyant work vest carried under the permissive authority of this section must be approved under—

- (1) Subpart 160.053 of this chapter; or
- (2) Subpart 160.077 of this chapter as a commercial hybrid PFD.

[CGD 78-174A, 51 FR 4350, Feb. 4, 1986]

§ 97.34-10 Use.

(a) Approved buoyant work vests are considered to be items of safety apparel and may be carried aboard vessels to be worn by crew members when working near or over the water under favorable working conditions. They shall be used under the supervision and control of designated ship's officers. When carried, such vests shall not be accepted in lieu of any portion of the required number of approved life preservers and shall not be substituted for the approved life preservers required to be worn during drills and emergencies.

§ 97.34-15 Shipboard stowage.

(a) The approved buoyant work vests shall be stowed separately from the regular stowage of approved life preservers.

(b) The locations for the stowage of work vests shall be such as not to be easily confused with that for approved life preservers.

§ 97.34-20 Shipboard inspections.

(a) Each work vest shall be subject to examination by a marine inspector to determine its serviceability. If found to

be satisfactory, it may be continued in service, but shall not be stamped by a marine inspector with a Coast Guard stamp. If a work vest is found not to be in a serviceable condition, then such work vest shall be removed from the vessel. If a work vest is beyond repair, it shall be destroyed or mutilated in the presence of a marine inspector so as to prevent its continued use as a work vest.

§ 97.34-25 Additional requirements for hybrid work vests.

(a) In addition to the other requirements in this subpart, commercial hybrid PFD's must be—

(1) Used, stowed, and maintained in accordance with the procedures set out in the manual required for these devices by § 160.077-29 of this chapter and any limitation(s) marked on them; and

(2) Of the same or similar design and have the same method of operation as each other hybrid PFD carried on board.

[CGD 78-174A, 51 FR 4350, Feb. 4, 1986]

Subpart 97.35—Logbook Entries

§ 97.35-1 Application.

(a) Except as specifically noted, the provisions of this subpart shall apply to all vessels other than motorboats and barges. Motorboats on an international or intercoastal voyage may be required to carry a logbook in accordance with § 97.35-10.

§ 97.35-3 Logbooks and records.

(a) The master or person in charge of a vessel that is required by 46 U.S.C. 11301 to have an official logbook shall maintain the logbook on form CG-706. When the voyage is completed, the master or person in charge shall file the logbook with the Officer in Charge, Marine Inspection.

(b) The master or person in charge of a vessel that is not required by 46 U.S.C. 11301 to have an official logbook, shall maintain, on board, an unofficial logbook or record in any form desired for the purposes of making entries therein as required by law or regulations in this subchapter. Such logs or records are not filed with the Officer in Charge, Marine Inspection, but must be

kept available for review by a marine inspector for a period of 1 year after the date to which the records refer. Separate records of tests and inspections of fire fighting equipment must be maintained with the vessel's logs for the period of validity of the vessel's certificate of inspection.

[CGD 95-027, 61 FR 26007, May 23, 1996]

§ 97.35-5 Actions required to be logged.

The actions and observations noted in this section shall be entered in the official log book. This section contains no requirements which are not made in other portions of this subchapter, the items being merely grouped together for convenience.

(a) Onboard training, musters, and drills: held in accordance with subchapter W (Lifesaving appliances and Arrangements) of this chapter.

(b) Steering Gear, Whistle, and Means of Communication. Prior to departure. See § 97.15-3.

(c) Drafts and Load Line Markings. Prior to leaving port, ocean, coastwise, and Great Lakes services only. See § 97.15-5.

(d) Verification of vessel compliance with applicable stability requirements. After loading and prior to departure and at all other times necessary to assure the safety of the vessel. See § 97.15-7.

(e) Loading doors. Where applicable, every closing and any opening when not docked. See § 97.15-17.

(f) Hatches and other openings. All openings and closings, or leaving port without closing. Except vessels on protected waters. See § 97.15-20.

(g) Emergency Lighting and Power Systems. Weekly and semi-annually. See § 97.15-30.

(h) Fuel oil data: Upon receipt of fuel oil on board. See § 97.15-55.

(i) Cargo gear inspections: At least once a month. See § 91.37-70 of this subchapter.

(j) Inflatable hopper gate seals. Where installed to comply with subpart G of part 172 of this chapter after each carriage of cargo. See § 97.15-75.

[CGFR 65-50, 30 FR 17011, Dec. 30, 1965, as amended by CGD 80-159, 51 FR 33059, Sept. 18, 1986; CGD 89-037, 57 FR 41823, Sept. 11, 1992; CGD 84-069, 61 FR 25289, May 20, 1996]